



THE ARALUEN ARTS CENTRE
THEATRE TECHNICAL SPECIFICATIONS
2021

DIRECTOR:	FELICITY GREEN
TECHNICAL MANAGER:	Nathan Sopeer e: nathan.sopeer@nt.gov.au p: 08 8951 1155
THEATRE TECHNICIAN:	Letitia Firth e: letitia.firth@nt.gov.au p: 08-89511149

Reference points for measurements are:

HEIGHT	:	Relative to stage floor
DEPTH	:	Relative to apron of stage
THROW	:	Relative to centre of apron at 180mm above stage
ANGLE	:	Relative to horizontal at 180mm above stage

Tel: 08 8951 1120
Fax: 08 8953 0259
E-mail: araluen@nt.gov.au

Website: <http://araluenartscentre.nt.gov.au/>

Mail: PO Box 3521
ALICE SPRINGS NT 0871

Address: 61 Larapinta Drive
ALICE SPRINGS NT 0870

THEATRE DIMENSIONS

Proscenium	Width	12.930 metres
	Height	6.745 metres
Stage Width	Wall to wall	21.40 metres
	Centre Line to PS wall (c'weight frame)	9.95 metres
	Centre Line to OP wall	10.70 metres
Stage Depth	Apron to rear of Proscenium wall	0.620 metres
	Apron to rear of fire curtain guides	0.820 metres
	Apron to House Curtain line	1.020 metres
	Apron to line 1	1.265 metres
	Apron to line 60 (last c'weight set)	10.415 metres
	Apron to back wall	11.615 metres
Stage Height	To underside of headblock steels	18.68 metres
	To underside of grid floor	16.68 metres
	To underside of grid steels	16.47 metres
	To loading gallery floor	15.35 metres
	To underside of fly floor	6.740 metres
	Floor to batton (out dead)	16.30 metres
	Floor to batton (in dead)	00.65 metres
	Drift	15.65 metres
Width between Fly Galleries		17.70 metres
Stage Floor	Tempered Masonite screwed over Pinus Radiata floor, full width.	
	No level change	
	No rake	
	Load rating	750 kg/sq m
Stage Trap	5.72 metres upstage of apron on centre line.	
	2 halves each 860mm deep x 700mm wide.	
	Total opening available unobstructed	
	is 860 mm deep x 1500mm wide.	
Orchestra Pit/Lift	The theatre has a 3 position (pit/auditorium/stage) trapezoid shaped orchestra pit/lift, which extends from the stage apron to 2.490 metres into the auditorium. Along the upstage edge the lift is 10.690 metres wide; along the downstage edge it is 6.500 metres wide.	
	Lift floor at auditorium level = stage -0.830 metres	
	Lift floor at full pit level = stage -2.690 metres	
	Max. Working load = 8 Tonne.	
	Max. Floor loading = 750 kg/sq. m.	
	Max. Point load = 1100 kg/sq. m.	
Juliet Balconies	2.4 metres above stage level, over forestage access doors.	
	Concealed when not in use by two sets of bifold doors, each set 1.2 m wide x 2 m high. The doors conceal a proscenium perch lighting position.	
Forestage Access	Doors either side of the proscenium arch gives access to forestage. 1.2 m wide x 2.4 m high.	
Stage Access Door	To Loading Dock	
	Height	6.55 metres
	Width	2.40 metres
	Maximum Diagonal	6.90 metres

Araluen Arts Centre, Alice Springs	Theatre Technical Specifications
------------------------------------	----------------------------------

Loading Dock	Ceiling Height - Maximum	12.20 metres
	Minimum	4.90 metres
	Floor space available	110.00 sq metres
Loading Dock Access Door (External)	Height	3.20 metres
	Width	2.40 metres
	Maximum Diagonal	4.00 metres
Vehicle Access to Loading Bay	Enter via Larapinta Drive and use western loop road to loading bay. Dock is 1.2 metres above driveway level. Loading bay is covered and will accommodate vehicles to 4.5 metres in height.	

STAGE MACHINERY

Counterweight System	45 of 60 single purchase 5 line counterweight sets installed on P.S. See hanging plot for spacing of lines. All lines have a WWL = 500 kgs.	
Cradle Capacity	Single cradle (no extender cradle fitted) maximum lift is 395kgs, including bar weight. With cradle extenders fitted maximum lift is 500 kgs, including bar weight.	
Standard Batten	Steel Pipe - 48mm O.D. Length - 16 metres	
Fly line pickups	5 lines per bar: pickups @ Centre, then 3600mm & 7200mm to OP & PS	
Fire Curtain	Semi rigid sheet steel construction with motorized winch.	
House Curtain:	Variable speed motorized single axis hoist with Jands SAX-P1 controller controlled from Prompt Corner. Can also be operated as a motorised French action tabtrack controlled from Prompt Corner and from Control Room. Line situated 1020mm from apron. Colour: Ochre	
Stage Drapery	<p><u>Tabs:</u> 2 sets Black Velour on manually operated heavy duty tab tracks. Each half 8.3m wide 8.3m drop (with fullness) 1 sets Black Velour <u>not on tracks</u>. Each half 8.3m wide 8.3m drop (with fullness)</p> <p><u>Legs:</u> 5 pairs Black Velour each 4.3m wide x 8.2m drop (with fullness)</p> <p><u>Borders:</u> 5 only Black Velour each 16m wide x 3.5m drop (with fullness)</p> <p><u>Teaser:</u> 1 only Black Velour 16m wide x 3.5m drop (Flat)</p> <p><u>Cyclorama:</u> 1 only White filled cloth 16m wide x 8m drop.</p> <p><u>Scrim:</u> 1 only White Sharks Tooth Gauze 15m wide x 7m drop. 1 only Black Sharks Tooth Gauze 15m wide x 7m drop.</p>	

SCENERY / STAGING

Portable Staging

27 x Prostage Portable Staging units. All sections 2.0m x 1.0m with following heights available:

	<u>Theatre</u>	<u>Witchettys</u>	<u>Total</u>
Modular Series Variable Height 800-1200mm	3 Units	0 Units	3 Units
Riser Series Variable Height 400-600mm	8 Units	0 Units	8 Units
Riser Series Fixed Height 400mm	0 Units	4 Units	4 Units
Riser Series Fixed Height 200mm	4 Units	0 Units	4 Units
Riser Series Deck Only	3 Units	5 Units	8 Units
Total	<u>18 Units</u>	<u>9 Units</u>	<u>27 Units</u>

Riser Series Variable Height 1.0m x 1.0m	1 Unit
4m Long Truss Frame	6 Units
2m Gates for Truss Frame	10 Units
1m Gates for Truss Frame	8 Units
2m Guard Rails	8 Units
1m Guard Rails	6 Units
4 Rise Step Unit (+800mm Stage)	2 Units
2 Rise Step Unit (+400mm Stage)	2 Units
Extra Step Unit (+200mm Stage)	2 Units

Canvas Flats	10 Pieces @ 5500mm x 1800mm. (Condition fair to poor)
Black Wool Flats	8 Pieces @ 5500mm x 1800mm
Bleacher Units max.	4 x Pongrass Tiered Retractable seating units, each to hold 26 persons (4100mm wide x 3400mm deep x 1800mm high, when extended)
Dance Floor	Colour: Light Grey, 7 rolls 1500mm deep, 1 cut roll to fit Proscenium Arch Coverage: Full stage

HANGING PLOT - STOCK RIG

Line No		Depth (mm from apron)
	Rear Proscenium Wall	0715
	Rear of Fire Curtain Guides	0815
HC	House Curtain	1015
1	Teaser	1265
2	Spare	1415
3	Spare	1565
4	Lighting Bar - No. 1	1715
5	SPACE FOR STRUCTURAL SUPPORT OF HC MOTOR	
6	Spare	2015
7	Spare	2165
8	Spare	2315
9		Not Installed
10	Border - No. 1	2615
11	Legs - No. 1	2765
12	Spare	2915
13		Not Installed
14	Spare	3215
15	Spare	3365
16		Not Installed
17	Lighting Bar - No. 2	3665
18		Not Installed
19	Spare	3965
20	Spare	4115
	SPACE FOR STRUCTURAL SUPPORT	
21	Spare	4415
22	Border - No. 2	4565
23	Legs - No. 2	4715
24	Black Tab - No. 1	4865
25		Not Installed
26	Cinema Screen (NOT MOVEABLE)	5165
27	Spare	5315
28	Spare	5465
29		Not Installed
30	Lighting Bar - No. 3	5765
31		Not Installed
32	Spare	6065
33	Spare	6215
34	Spare	6365
35	Spare	6515
36	Spare	6665
37		Not Installed
38	Border - No. 3	6965
39	Legs - No. 3	7115
40		Not Installed
41	Black Tab - No. 2	7415
42	Spare	7565
43		Not Installed
44	Lighting Bar - No. 4	7865
	SPACE FOR STRUCTURAL SUPPORT	
45	Spare	8165
46	Spare	8315
47		Not Installed
48	Border - No. 4	8615
49	Legs - No. 4	8765
50	Spare	8915
51		Not Installed

Araluen Arts Centre, Alice Springs		Theatre Technical Specifications
52	Lighting Bar - No. 5 (Flood Bar)	9215
53		Not Installed
54		Not Installed
55	Spare	9665
56	Spare	9815
57	Spare	9965
58	Black Tab - No. 3	10115
59	Spare	10265
60	Cyclorama	10415

Please note:

1) Legs on above lines give the most effective mask into the wings. The fan shape of the auditorium can make side masking quite difficult. Legs 1, 2 & 3 have returns downstage of approx. 1100 mm.

2) In the case of lighting bars, if the distance to the next bar, up or down stage, is 150mm then that bar should be left free. (I.e. for stock rig line 3 should be left free)

LIGHTING

Control Desks	ETC Ion XE 2k
	Strand 300 Series. 250 channel with 72 submasters. Full function wireless remote.
	Strand GSX with Genius 125 and Kaleidoscope software. Full function Designers remote.
Control Protocols	DMX 512
DMX Inlets/Outlets	2 x DMX Loops with inputs/outputs distributed from PS Fly Floor. DMX IN: Control room & Centre Auditorium. DMX OUT: Dimmer Rm, OP Fly Floor, Stage - D/S OP, D/S PS, U/S OP & U/S PS, and M/S Floor Trap PS & OP.
DMX Splitters	2 x Jands DD8 opto-isolated DMX splitter.
DMX Wireless	1 x CRMX Nova FX 2.4GHz
Multiplexers	2 only LSC Linklight 48 channel multiplexers D/A Converter
Dimmers	Total number of dimmers = 228 comprising: <u>Dimmer Room</u> (adjacent to fly gallery USPS): 3 x Jands HP12-SCWM (Digital): 2.5 kW 8 x Jands HP6-WM (Digital): 5 kW 3 x Jands HPC12-SCR (Digital): 2.5 kW <u>OP Fly Floor:</u> 4 x Jands HP12-SCWM (Digital): 2.5 kW 4 x Jands HPC12-SCR (Digital) 2.5 kW 1 x Jands HP6-WM (Digital): 5 kW <u>PS Stage Rear Wall:</u> 1 x Jands HP6-WM (Digital): 5 kW <u>Extras:</u> 2 x 2.4kW Strand Model 1 Portable Dimmers 1 x Jands 12ch Analog Rack
Lantern Stock	<u>Fresnels</u> 2 kW Strand Cadenza with B/D 6 2 kW Robert Juliat 329HF with B/D 12 1 kW Strand Harmony with B/D 24 1 kW CCT Starlette with B/D 20 1.2 kW Robert Juliat 310HF with B/D 60 1.2 kW Selecon with B/D 10 500W CCT Minuette with B/D (Curtain Warmers) 2 <u>Profiles</u> ETC Source 4 15/30 Zoom Profiles 60 ETC Source 4 25/50 Zoom Profiles 20 1 kW Strand Harmony 15/28 Permanently rigged as side booms 32 <u>LED</u> ETC S4 LED series 2 Lustr with CYC Adaptor 6 Robe Robin 800 LEDWash with Beam Shaper 1 <u>Floods</u> 1 kW Par 64 with 240v lamp 41

	1 kW Iris 4 Cyc Floods	5
	750w Strand Quartz Color Pallas 4 Ground Rows	5
	500w Nocturne Floods with B/D	6
	<u>Follow spots</u>	
	1.2kW MSD Robert Juliat Topaze with C/Mag	2
	<u>Effects Lighting</u>	
	U.V. Floods (Patt 60)	2
	U.V. Fluorescent Fittings	4
	Martin Atomic 3000 DMX Controllable Strobe	1
	450 mm Mirror Ball with rotator	1
Accessories	A number of iris' and gobo holders are available to suit all profiles (Aperture diameter 72mm suit size B gobos)	
	6m Aluminium Pipe	3
	5.5m Aluminium Pipe	4
	2m Steel Pipe	8
	Base Plates for stage booms	8
	Telescopic stands	5
	H stands	14
	Boom Arms	56
	Steel Scaffold Clamps 90°	10
	Steel Scaffold Clamps Swivel	9
	Aluminium Scaffold Clamps 90°	11
	Aluminium Scaffold Clamps Swivel	2
Smoke Machine	2 x MDG ATMe Haze Generator, DMX controlled	
Tallescope	1 x Instant scaffold No. 524 (platform height 4.6m to 7.5m) 1 x JLG 30AM Push Around Vertical Mast Lift.	
Auxiliary Power:	<u>150 amp 3-phase</u> : 2 Outlets for lugged or unlugged termination, located USPS rear stage wall and in loading bay area.	
	NOTE: Only one distribution point can be operated at a time. This supply is currently used to power 6 x 3-phase outlets for dimmers on the OP Fly Floor.	
3 Phase Power:	<u>32 amp 3-phase</u> : 5 pin WILCO WICM 530 outlets are located in Loading Dock, Loading Bay and Orchestra Pit PS. <u>40 amps 3-phase</u> : Dimmer Room x 5, On Stage x 3 - US OP & PS, DS OP.	

Lighting Positions

F.O.H. Lighting Bridges	<u>No.1 Bridge</u> Width 19.2m Patch outlets: 29 x 10 amp, 4 x 20 amp. Distance from apron 5.45m Height from stage floor to bar: 7.93m Throw to apron at stage floor: 9.65m Angle at apron: 56 degrees
	<u>No.2 Bridge</u> Width 19.2m Patch outlets: 26 x 10 amp, 4 x 20 amp. Distance from apron: 9.4m Height from stage floor to bar: 7.93m Throw to apron at stage floor: 12.29m Angle at apron: 40 degrees
F.O.H. Perches	Length 2.6m Patch outlets per side: 7 x 10 amp, 1 x 20 amp.

	<p>Throw from bottom to apron at centre stage: 12.96m Angle from bottom to apron at centre stage: 20.45 degrees. Throw from top to apron at centre stage: 13.93m Angle from top to apron (centre stage) 29.30 degrees</p>
F.O.H. Proscenium Booms	<p>(Located within top two doors of the P & OP Juliet Balconies) Height: From Stage +2400 to + 6000m Patch outlets per side: 7 x 10 amp, 1 x 20 amp.</p>
Stage	<p>There are 5 wired lighting bars which feed to the OP Fly Gallery.</p> <p><u>LX 1, 2 and 3</u> 24 x 10 amp, 6 x 20 amp circuits</p> <p><u>LX 4</u> 30 x 10 amp circuits</p> <p><u>LX 5 (Cyc flood bar)</u> 11 x 10 amp circuits (single outlets) 4 x 20 amp circuits (single outlets) 4 x 20 amp circuits each with 5 outlets per circuit</p>
Patch Panel	<p>203 Lighting outlets fully patchable via a master patch panel in Dimmer room</p>

Araluen Arts Centre, Alice Springs		Theatre Technical Specifications
Stage Patch Outlets	Fly Gallery PS No 1	4 x 10 amp, 1 x 20 amp
	Fly Gallery PS No 2	4 x 10 amp, 1 x 20 amp
	Fly Gallery PS No 3	4 x 10 amp, 1 x 20 amp
	Total circuits @ this position	15 circuits
	Fly Gallery OP No 1	19 x 10 amp, 1 x 20 amp
	Fly Gallery OP No 2	14 x 10 amp, 1 x 20 amp
	Fly Gallery OP No 3	14 x 10 amp, 1 x 20 amp
	Fly Gallery OP No 4	6 x 20 amp
	Total circuits @ this position	56 circuits
	Floor Wells PS No 1	4 x 10 amp
	Floor Wells PS No 2	4 x 10 amp
	Floor Wells PS No 3	4 x 20 amp
	Total circuits @ this position	12 circuits
	Floor Wells OP No 1	4 x 10 amp
	Floor Wells OP No 2	4 x 10 amp
	Floor Wells OP No 3	4 x 20 amp
	Total circuits @ this position	12 circuits
	Forestage Entrance PS	3 x 10 amp
	Forestage Entrance OP	3 x 10 amp
	Total circuits @ this position	6 circuits
	Orchestra Pit PS	1 x 10 amp
	Orchestra Pit OP	1 x 10 amp
	Total circuits @ this position	2 circuits
	Understage PS	2 x 10 amp
	Control Room	2 x 10 amp
		2 x 20 amp
	Total circuits @ this position	4 circuits
Power Distribution	1 x Jands PSD6R Distribution Unit: 6 x 20 Amps distribution unit.	

AUDIO EQUIPMENT

Sound Desks	<p><u>Soundcraft MH3</u> (situated at Auditorium Mixing Position)</p> <p>Configurable as FOH/Monitor/ or Monitor from FOH</p> <p>Inputs 32 mono inputs 4 Stereo inputs 4 band EQ on all input channels Insert points on all mono channels Direct out on all mono channels Phantom power on all mono channels Phase reverse on all mono channels LCR panning on all inputs</p> <p>Outputs 8 Groups/12 Auxiliaries (FOH Mode) 12 mono or 8 mono + 2 Stereo in Monitor Mode 8 VCA & Mute Groups with snapshot automation 12x4 Output Matrix Left, Right and Centre Mix out</p> <p><u>Presonus StudioLive 16 Series 3 Digital Console</u></p> <p>Inputs 24 total inputs 16 channel inputs: 8 mic, 8 mic / line 16 via USB and AVB 1 XLR Talkback mic input 2 stereo Aux inputs Unbalanced stereo (RCA) tape input and output Bluetooth [™] 4.1 wireless tape input</p> <p>Outputs 10 FlexMix outputs: 6 XLR, 4 balanced TRS Stereo AES / EBU digital output 2 XLR (L / R) Main outputs XLR Main summed mono output 2 TRS monitor outputs 26 buses: 16 FlexMixes (can be designated as aux, subgroup, or matrix mixes) 4 dedicated subgroups 4 internal effects sends Stereo main bus</p> <p>24 Filters DCAs for easy and flexible control groups of channels</p>
Signal Processing	<p><u>FOH</u> 2 x BSS Soundweb BLU-100 DSPs</p> <p><u>Foldback</u> 1 x DBX 480R Drive Rack 2 x DBX 480 Drive Racks</p>
Audio Patching	<p>Patching provided by an XLR patchbay located in the control room. 66 Individual balanced microphone points located around the stage. Stage to Control Room: 24 both-way patch field Control Room to FOH Position: 32 Sends & 16 Returns Control Room to Amp Rack: 7 both-way patch field & 6 Sends Amp Rack to Control Room Speaker Tielines: 6 Sends Control Room Mixing Position to Control Room Patch: 16 Sends & 8 Returns</p>

Araluen Arts Centre, Alice Springs		Theatre Technical Specifications	
Multi-core	2 x 12 both-way stage box & 20m tail 1 x 12 both-way stage box & 50m tail 1 x 12 way stage box with monitor split (all channels transformer isolated at mic level) with 10m tail 1 x 6 way stage box with monitor split (all channels transformer isolated at line level) with 10m tail 1 x 16 send & 4 return multicore @ 20 metres		
Speaker Outlets	38 Outlets: 10 FOH, 4 on orchestra lift, 20 onstage, 1 Juliet Balcony Entrance PS, 1 Juliet Balcony Entrance OP, 1 Fly Gallery PS, 1 Fly Gallery OP.		
Radio Microphones			
Shure ULX	6 only Shure ULXP4 Professional Diversity UHF Receivers 6 only Shure ULX1 Body-Pack Transmitters (TA4M connectors) 6 only Shure ULX2 Hand-Held Microphone Transmitter (SM58) (662.75 to 668.75 MHz) 2 only Shure UA844 Antenna Distribution Systems		
Shure UT4	3 only Shure UT4 Diversity Receiver (598.625, 600.800, 606.300MHz) 1 only Shure SM58 UT2 Hand Held Transmitter 2 only Shure UT1 Body Pack Transmitter with TA4M Socket		
Shure ULXD	1 only Shure ULXD4Q Quad Receiver L51 Band (632 to 696 MHz) 4 only Shure ULXD2 Hand-Held Microphone Transmitter (Beta58A) 2 only Shure ULXD1 Bodypack Transmitters 3 only Shure SBC200 Dual Drop-In Battery Charger 7 only Shure SB900A Rechargeable Battery		
Mic Accessories	2 only Shure WL93 Omnidirectional Subminiature Lavalier Microphone with TA4F Plug 8 only DPA 4066-F Omnidirectional Headband Microphones (Beige) with TA4F Plug		
Microphones	1 x Shure Beta 52A 4 x Shure SM57 6 x Shure SM58 4 x Shure Beta 56A 4 x Shure Beta 57A 4 x Shure Beta 58A 2 x Shure Beta 87A 2 x Shure SM99 - 12" gooseneck 2 x Shure MX418/C - 18" gooseneck 1 x Shure Easyflex EZG/18 - 18" gooseneck 4 x Shure MX202B/C 2 x Shure MX393/C Boundary Microphones 2 x AKG SE300B Preamps with CK93 Capsules 2 x AKG C451 B 4 x AKG C451 EB Pre-amp (2 used for program feed) 3 x AKG CK1 Capsules 1 x AKG CK5 Capsule 2 x AKG CK9 Capsules (Shotguns) (Used for program feed) 3 x AKG D330 BT 4 x Realistic PZM		
D.I.s	8 x BSS AR133 Active DIs 1 x Jands Active D.I. 4 x Hux Passive D.I.s 1 x ARX DI-4 Quad DI Box and Line Mixer		
Microphone Stands	15 x Sennheiser SEMS 3135 telescopic boom stands		

	6 x Beyer ST 600 round base upright stands 10 x Beyer short boom stands 3 x table stands
Playback / Recording	1 x Sony MDS 501 Minidisc recorder 2 x Denon DN-D4500 Double CD/MP3 Player 1 x Denon DN-700C CD/MP3/Ipod/Network Player 2 x Sony CDP 991 Compact Disc Player 1 x Sony CDP XE300 Compact Disc Player
Signal Processors	1 x Yamaha SPX 900 Multi-effects processor 1 x Yamaha SPX 2000 Multi-effects processor 1 x T.C. Electronics M-One XL Multi-effects processor 2 x DBX 1074 Quad Gates 3 x DBX 266XL Dual Channel Compressors/Gate 2 x DBX 266XS Dual Channel Compressors/Gate 1 x DBX 163X Over easy Compressor/Limiter 1 x Lexicon MPX200 Effects Generator
EQs	2 x Klark-Teknic DN3600C (30 band, dual channel) Programmable EQ 1 x Klark-Teknic DN 410 Parametric Equaliser 8 EQs in DBX 480 Drive Racks 3 x Yamaha Q 1027 1/3 Octave Graphic Equaliser
Amplifiers	2 x Crown CTS 3000 (FOH Subs) 2 x Lab.Gruppen FP6000Q (FoldBack) 1 x Crown CTS 600 (Cinema Surround) 2 x Crown CTS 600 (Spare) 4 x Crown CTS 2000 (Spare)
Speakers	<u>F.O.H.</u> 3 x Meyer UPQ-1P Wide Coverage Loudspeakers (Powered) 2 x JBL AL6125 Subs <u>F.O.H Front Fill</u> 4 x Meyer UPM-1P (Powered) (Mounted in Stage Apron) <u>Foldback</u> 8 x Nexo PS10 with PS10TD controllers 6 x JBL MP212 Wedges 3 x Aust Monitor wedges FB300 15" + coaxial horn <u>Cinema Surround</u> 1 x 802C Bose Active processor 4 x Bose 802 <u>Control Room Monitoring</u> 2 x JBL LSR25P Self Powered
Headphones	1 Pair AKG K 501

ORCHESTRA EQUIPMENT

1 x RAT Conductor's Stand
 20 x RAT Orchestra Stands
 6 x Black Orchestra Chairs

PIANOS

1 x Yamaha CF Concert Grand – 9ft SN:3750200
2 x Victor VG62 Baby Grands – 5ft SN:045023 & SN:048018
2 x Yamaha U1 Professional Uprights – 4 ft SN:A3833852 & SN:A3833869

PROJECTION EQUIPMENT**Cinema screen**

1 only Harkness matt white screen (1.4 gain) with fixed top masking to maximum picture size:

<i>Cinemascope:</i>	8930mm wide x 3800mm high. (2.35:1 ratio)
<i>Cinema Flat:</i>	7030mm wide x 3800mm high. (1.85:1 ratio)
<i>16:9 widescreen:</i>	6755mm wide x 3800mm high. (1.77:1 ratio)
<i>4:3 ratio:</i>	5066mm wide x 3800mm high. (1.33:1 ratio)

Video/Data Projector

1 x NEC NC-1200C Digital D-Cinema Projector (2k Res) with GDC SX200A/R IMB & GDC 3TB Server with Touch Screen. Lens NC-60LS19Z 2.5/41.6-71.1mm. Throw Ratio 1.90 - 3.25:1.

1 x Panasonic PT-DW6300 digital projector with standard (TKGF0109-5 with 1.8-2.4:1 Throw Ratio) and long throw (ET-DLE 250 with 2.4-3.8:1 Throw Ratio) zoom lens.

* Please note additional hire charges apply for use of these projectors.

Switcher/Scaler

1 x Analogway Pulse PLS300: 8 x Universal Inputs, 2 DVI inputs, 2 x SDI inputs with dual outputs Live & Preview (VGA+DVI) Output Resolution up to 2k.

1 x Analogway Octofade: Computer & Video A/V Seamless Switcher, Fading & Titling Effects.
8 x Universal Inputs with 1 x VGA output: up to 1400x1050 (SXGA+)

AV Accessories**Computers**

1 x 23inch IMac with Qlab3
1 x MacPro with Qlab3

Audio Interface

Motu828x (USB & Thunderbolt Connection)

Monitors

4 x Response QM-3752 video monitors (7 inch)
3 x 23inch widescreen monitors (1080p)
1 x 24inch widescreen monitors (1080p)

Remotes

1 x Leon Audio Power Point Remote Controller
1 x MircoCue 2L Wireless Power Point Remote

Splitters

1 x ATEN 4 way VGA Splitter
1 x ATEN 2 way VGA Splitter
1 x 4 way DVI Splitter
2 x 2 way DVI Splitter

Cable

1 x 50m DVI Fibre Optic Cable (Stage to Control Rm)
1 x 15m DVI Cable
2 x 10m DVI Cable
5 x 5m DVI Cable
1 x 50m VGA Cable
2 x 10m VGA Cable
Various 1m VGA Cables

Extenders

2 x Abtus CAT-GA11MT/AP3 VGA to Cat5 TX Extender
2 x Abtus CAT-GA111R/AP3 Cat5 to VGA RX Extender

Video Processors

1 x Kramer VP-200DXL Differential Amplifier/DA

Video & DVD players

1 x JVC BRS600E VHS Video Recorder
2 x Pioneer DVD-V8000 DVD Player
1 x Pioneer BDP-V600 Blu-ray Player

Conference Phone

Polycom Sound Station Duo VoIP/PhoneLine

Screens

2 x 1800mm x 2400mm White MDF Boards (Freestanding / Flyable)

White Boards

2 x Portable freestanding white boards

DIGITAL VIDEO FORMATS

Araluen's preferred digital formats for presentation in-house are:

For images: JPEG or PNG with a minimum pixel resolution of 1920 wide x 1080 high (16:9 ratio)

For video files: QuickTime h264 with a minimum pixel resolution of 1920 wide x 1080 high (16:9 ratio)

For Cinema Film: DCP-JPEG 2000 2K resolution in either Flat (1998 x 1080, 1.85:1) or Scope (2048 x 858, 2.39:1)

FACILITIES

Dressing Rooms	<p>No. 1 & 2 for 29 artists. Each room 7.8m x 7.5m No. 3 & 4 for 4 artists. Each room 2.4m x 3.7m All with individually lit make-up benches All with separate shower and toilet facilities All with Program Relay & CCTV monitors 6 x Large costume rack trolleys, length 1900mm 2 x Medium costume rack trolleys, length 1000mm 2 x Small costume rack trolleys, length 750mm</p>
Tour/Production Office	1 x Office 3.8m x 2.1m
Laundry	<p>3.7m x 4.6m. Equipped with the following items 1 x 7kg automatic washing machine 1 x 5kg tumble drier 1 x Cabinet drier 1 x Ironing board & Iron 1 x Washing Tub</p>
Green Room	<p>3.5m x 4.6m equipped with refrigerator, microwave and Rheem Laser boiling water unit <u>NOTE:</u> Araluen does not supply tea/coffee etc.</p>

STAGE MANAGEMENT

S.M. Console	Located in prompt corner with dedicated talkback to all production areas, CCTV, telephone and paging to all backstage areas and control room.
Talkback System	<p>Telex Audiocom US2000 Microprocessor controlled two-channel intercom system with S.M. communication points in all production areas.</p> <p>1 x US-2000 Station + SPS-2000 Power Supply. 7 x Telex BP-1000 Belt-packs with PH-1 single ear headsets. 4 x Telex/RTS BP-1002 Belt-packs with HR1 single ear headset.</p> <p>1 x Telex/RTS BTR-240 Wireless Intercom Base Station 4 x Telex/RTS TR-240 Wireless Belt-pack with HR-1 single ear headset.</p> <p>1 x Telex RadioCom BTR-700 UHF Wireless Intercom Base Station. 4 x TR-700 UHF Belt-packs with PH-1 single ear headsets.</p>
Closed Circuit TV	<p>1 x Panasonic AW-HE60 PTZ colour camera mounted at rear of Auditorium giving a full stage picture. Colour monitors located at the SM console, PS and OP wings, all Dressing rooms and Green Room and Touring Company Production Office.</p>
Paging System	Paging to all backstage & production areas as well as program relay.
Internet Access	Internet Access available upon request throughout Theatre & Backstage via Wifi & Ethernet connection.